

DRYER DATA SHEET

Refrigerant Dryers

MODEL DATA				
1	Manufacturer	Industrial Technologies & Services KOREA		
2	Date	December 08, 2025		
3	Model Number	FLXA12.5-W		
4	Cycling/Non-Cycling	Cycling		
5	Refrigerant Type	R454c		
6	Air/Water Cooled	Water		
7	Voltage	460/3/60		
	DESCRIPTION	FULL FLOW	10% FLOW	UNITS
8	Tested Flow ^a	1250	125	scfm ^b
9	Outlet Pressure Dew Point	43.7	39.7	°F
10	Pressure Drop	4.81	0.09	psi(d)
11	Total Dryer Input Power	6.1	0.61	kW
12	Specific Package Power ^c	0.49	0.49	kW/100 scfm

Notes:

a. Dryer ratings at the following inlet conditions to the dryer (as per adopted CAGI Standard ADF 100):

- Inlet Compressed Air Temperature: 100°F (37.78°C)
- Inlet Compressed Air Pressure: 100 psig (6.9 Bar)
- Max. Ambient Air Temperature: 100°F (37.78°C)
- Inlet Compressed Air Relative Humidity: 100% (Saturated)

b. SCFM defined as the volume of free air in cubic feet per minute measured at 14.5 psia (1.0 Bar), 68°F (20°C) temperature and 0% R.H. (0 WVP).

c. (Total Dryer Input Power/tested flow) x 100

Member



This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.