# **LP SERIES - 115 VOLT 60HZ**



## FEATURES

- > Low sound level
- > Low vibration
- > Low pulsations
- > Low power consumption
- > Oil-less operation
- > Integral intake filter
- > Few moving/wearing parts
- > Protection class IP54

## BASE MODEL

- LP-150HN
- LP-200HN



LP Series

## TYPICAL APPLICATIONS

- > Sewage aeration
- > Pond aeration
- > Aquaculture
- > Custom water features
- > Air pillow packaging




# **LP SERIES - 115V 60HZ**

Flow	Up to 7.7 cfm
Max. pressure	Up to 4.35 psi
Max. vacuum	N/A



#### Pump Flow and Pressure



Operation outside specified operating range is not recommended

PNEUMATIC DATA			
Description	LP-150HN	LP-200HN	
Part number	150141	150144	
Rated pressure	3.05 psi	3.05 psi	
Flow at rated pressure	5.09 cfm	6.89 cfm	
Operating range	1.45 to 4.35 psi	1.45 to 4.35 psi	

ELECTRICAL DATA				
Motor type	Linear drive	Linear drive		
Nominal Voltage	115V 60Hz	115V 60Hz		
Consumption at rated pressure	1.5A / 126W	L2.8A / 212W		
GENERAL DATA				
Ambient temperature	14°F - 104°F	14°F - 104°F		
Safety certification	UL listed	UL listed		
Protection class	IP54	IP54		
Weight	19 lbs	19 lbs		
Outlet diameter	0.71"	0.71"		
Average sound level	41 dB(A)	42 dB(A)		
SERVICE PARTS				
*Maintenance rebuild kit	700605	700605		
Air filter	641871	641871		

All listed values are measured at standard atmospheric conditions.

### SERVICE PARTS

Maintenance rebuid kit consists of:


- 2 x Pump head with valves


- 2 x Diaphragm assembly 2 x Diaphragm nut 2 x Diaphragm washer Manual
- 1 x Air cleaner element
- 1 x Air cleaner gasket
- 1 x Cover plate gasket

### SUPPLIED AS STANDARD

- 1 x straight rubber hose 1 x 1.14" hose connector clamp 1 x 0.87" hose connector clamp 1 x air tap hose barb 2 Manual

#### PRODUCT DIMENSIONS





<sup>\*</sup>Maintenance Rebuild Kit denotes part is only available for trained service personnel. Contact your local sales representative.

