

## 2668 Series

### FEATURES

- > Custom configured part options
- > Oil-less operation
- > Permanently lubricated bearings
- > Stainless steel valves
- > Die-cast aluminum components
- > Dynamically balanced
- > Proven WOB-L technology
- > Monolithic head
- > Field service capability
- > Thermally protected motor
- > Designed and tested per Agency standards
- > RoHS compliant

Declaration documentation available upon request

### TYPICAL APPLICATIONS


- > O<sub>2</sub> Concentrator
- > Blood & Laboratory Analyzers
- > Aspirators/Respirators
- > Dental & Optical Equipment
- > Industrial/Manufacturing Equipment
- > Business Equipment/Food & Beverage Equipment

### BASE MODELS

2668E44XNTLSXX  
(115/60/1)

2668N44XNTLSXX  
(220-240/50/60/1)

2668S44XNTLSXX  
(100/50/60/1)





WOB-L

# 2668 Series

<b>Flow</b>	<b>3.1 cfm (87.8 l/min)</b>
<b>Max. pressure</b>	<b>100 psi (6.9 bar)</b>
<b>Max. vacuum</b>	<b>93% local barometer</b>

## CONFIGURED OPTIONS

- > Stroke
- > Pump restart
- > Head port thread
- > Foot tap thread
- > Electrical cord
- > Fan guard
- > Protective coating



See Performance Data for base model maximum operating pressures  
Consult factory for custom configured stroke options

NOTE: All test values are nominal and for reference only. They are not guaranteed maximum or minimum limits, nor do they imply mean or median values.


PERFORMANCE DATA	T10-0138	T10-0142		10-0140	
Model Number	2668E44XNTLSXX	2668N44XNTLSXX		2668S44XNTLSXX	
Head Configuration	Pressure/vacuum parallel flow	Pressure/vacuum parallel flow		Pressure/vacuum parallel flow	
Stroke	0.44 in. (11.2 mm)	0.44 in. (11.2 mm)		0.44 in. (11.2 mm)	
Nominal voltage input	115/60/1	230/50/1	230/60/1	100/50/1	100/60/1
Max. open air flow	3.1 cfm (87.8 l/min)	2.6 cfm (73.6 l/min)	3.1 cfm (87.8 l/min)	2.6 cfm (73.6 l/min)	3.1 cfm (87.8 l/min)
Max. rated pressure	100 psi (6.9 bar)	100 psi (6.9 bar)	100 psi (6.9 bar)	100 psi (6.9 bar)	40 psi (2.8 bar)
Current at rated pressure	4.5A	1.8A	2.1A	4.6A	4.3A
Power at rated pressure	489W	408W	449W	430W	432W
Speed at rated pressure	1699 rpm	1406 rpm	1676 rpm	1400 rpm	1689 rpm
Max. pressure restart	Consult factory	Consult factory		Consult factory	
Max. vacuum	93% local barometer	93% local barometer		93% local barometer	
Max. vacuum restart	Consult factory	Consult factory		Consult factory	

ELECTRICAL DATA	T10-0138		T10-0142		10-0140	
Motor type (Capacitance)	P.S.C. [15 µF]		P.S.C. [15 µF]		P.S.C. [20 µF]	
Motor locked rotor current	16.2A		5.9A	5.6A	10.9A	10.5A
Motor insulation class	B		B		B	
Thermal switch (Open temperature)	Yes [293°F (145°C)]		Yes [275°F (135°C)]		Yes [293°F (145°C)]	
Lead wire color, gauge	Brown(hot), blue(neutral), 18 AWG		Brown(hot), blue(neutral), 18 AWG		Brown(hot), blue(neutral), 18 AWG	
Capacitor lead wire color, gauge	Black, black, 18 AWG		Red, red, 18 AWG		Black, black, 18 AWG	

GENERAL DATA	T10-0138		T10-0142		10-0140	
Operating ambient temperature	50° to 104°F (10°C TO 40°C)*		50° to 104°F (10°C TO 40°C)*		50° to 104°F (10°C TO 40°C)*	
Safety Certification	cRUus		TUV		None	
Net weight	16.3 lbs (7.4 kg)		16.3 lbs (7.4 kg)		16.3 lbs (7.4 kg)	

\*Broader ambient operating ranges may be possible depending on your specific application. Please consult factory regarding your particular system needs.

## PRODUCT DIMENSIONS



PUMP AND COMPRESSOR SOLUTIONS FOR OEMS WORLDWIDE

[thomaspumps.com](http://thomaspumps.com)



**Gardner Denver Thomas GmbH**

Livry-Gargan-Str. 10  
82256 Fürstfeldbruck  
Germany  
T +49 8141 2280 0  
F +49 8141 8892136  
[thomas.de@irco.com](mailto:thomas.de@irco.com)

**Gardner Denver Thomas Pneumatic Systems (Wuxi) Co. Ltd.**

1 New Dong'an Road, Shuofang Town  
Xinwu District, Wuxi  
Jiangsu, 214142 China  
T +86 510 6878 2258  
F +86 510 6878 2200  
[thomas.cn@irco.com](mailto:thomas.cn@irco.com)

**Gardner Denver Thomas, Inc.**

1419 Illinois Avenue  
Sheboygan, WI 53081  
USA  
T +1 920 4574891  
F +1 920 4514276  
[td.usa@irco.com](mailto:td.usa@irco.com)

The information presented in this material is based on technical data and test results of nominal units. It is believed to be accurate and reliable and is offered as an aid to help in the selection of Thomas products. It is the responsibility of the user to determine the suitability of the product for the intended use and the user assumes all risk and liability in connection there with. Thomas does not warrant, guarantee or assume any obligation or liability in connection with this information.

Models presented in this catalog are representative of the product family. Photos of products pictured in this catalog do not necessarily represent a specific model number. To obtain further information for custom options, contact your local Thomas office.

Printed in U.S.A Form No. 850-4007 08/2024 © Gardner Denver Thomas, Inc. All rights reserved.