

UCON

D250-98

UCON fluids produced by Union Carbide Corp. are polyalkylene glycol fluids. The UCON-LB series is used as a lubricant base in automotive brake fluids and is also compounded to serve as lubricating and preservative coating for hydraulic base components. UCON LB-300X is an effective lubricant in vacuum pumps used in automotive assembly for automatic filling of the brake system. Unlike conventional pump oils this fluid is fully compatible with brake fluid.

PHYSICAL PROPERTIES		LB-300X	LB-400X
Viscosity	@ 100°F	300 SUS (65 CST)	400 SUS
	@ 210°F	62.7 SUS (11 CST)	74.3 SUS
Viscosity Index		174	179
Pour Point		-40°F	-30°F
Density @ 100°F		0.979 g/cc	0.981 g/cc
Vapor Pressure @ 68°F		<.001 Torr	<.001 Torr
Flash Point, PM CC		378°F	423°F
Fire Point, COC		585°F	595°F

Sold in the following container sizes:***LB-300X***

- 1 Quart – Part No. 203030-0000
- 1 Gallon – Part No. 203031-0000 (8 lbs)
- 5 Gallon – Part No. 203032-0000 (41 lbs)
- 55 Gallon – Part No. 203033-0000 (449 lbs)

LB-400-X

- 1 Gallon – Part No. 203034-0000 (8 lbs)
- 5 Gallon – Part No. 203035-0000 (42 lbs)
- 55 Gallon – Part No. 203036-0000 (454 lbs)

REF. PUMP TEST TAG NO. 807919

CONTACT US

For more information, contact your
Regional Sales Manager or call us at:

1-800-825-6937

Your Local Sales Professional: