



Ingersoll Rand®

Precision Lifting with Advanced Control.

The **E-Lift Series Electric Hoist** delivers smooth, precise lifting through advanced permanent magnet motor technology combined with VFD control. A unique, pendant-mounted control knob enables infinitely variable low-speed adjustment within the dual-speed operation, giving operators unmatched accuracy for delicate positioning, along with the productivity of standard high-speed lifting.

Engineered for demanding environments, the E-Lift features a rugged cast aluminum housing with integrated cooling fins for superior heat dissipation. With IP55 protection for the hoist and IP65 for the pendant, it ensures reliable performance, durability, and reduced maintenance in tough industrial applications.

E-Lift Series

Electric Hoist



Ingersoll Rand®
E-Lift Series
 Electric
 Hoist

Permanent magnet motor

IP55 hoist / IP65 pendant

Capacities from ½-Ton to 5-Ton

Electro-Galvanized Link Chain

Aluminum Housing

Two-button Pendant

Dual-speed operation



Model Number	Capacity (lbs)	Duty Rating HMI (FEM)	Lifting Speed (ft/min)		Product Weight (lbs.)	Rated Power (hp)	Headroom in (mm)
			Low (Variable)	High			
EVLK0501C10C06102L	1102	H4/M5 (40m)	6.6 - 17	33	94	1.5	22.8 (580)
EVLK1001C10C06102L	2205	H4/M5 (40m)	5.2 - 14	26	102	2.0	22.8 (580)
EVLK1002C10C06102L	4409	H4/M5 (40m)	2.6 - 6.9	13	110	2.0	24.4 (620)
EVLK2001C10C06102L	4409	H4/M5 (40m)	6.2 - 12	31	209	5.0	40.2 (1020)
EVLK2501C10C06102L	5512	H4/M5 (40m)	5.2 - 10	26	224	5.0	40.2 (1020)
EVLK1502C10C06102L	6614	H4/M5 (40m)	4.3 - 8.5	21	246	5.0	41.3 (1050)
EVLK2502C10C06102L	11023	H4/M5 (40m)	2.6 - 5.2	13	297	5.0	43.3 (1100)
EVLK0501C03C03036L	1102	H4/M5 (40m)	6.6 - 17	33	94	1.5	22.8 (580)
EVLK1001C03C03036L	2205	H4/M5 (40m)	5.2 - 14	26	102	2.0	22.8 (580)
EVLK1002C03C03036L	4409	H4/M5 (40m)	2.6 - 6.9	13	110	2.0	24.4 (620)
EVLK2001C03C03036L	4409	H4/M5 (40m)	6.2 - 12	31	209	5.0	40.2 (1020)
EVLK2501C03C03036L	5512	H4/M5 (40m)	5.2 - 10	26	224	5.0	40.2 (1020)
EVLK1502C03C03036L	6614	H4/M5 (40m)	4.3 - 8.5	21	246	5.0	41.3 (1050)
EVLK2502C03C03036L	11023	H4/M5 (40m)	2.6 - 5.2	13	297	5.0	43.3 (1100)



Ingersoll Rand (NYSE:IR), driven by an entrepreneurial spirit and ownership mindset, is dedicated to helping make life better for our employees, customers, and communities. Customers lean on us for our technology-driven excellence in mission-critical flow creation and industrial solutions across 40+ respected brands where our products and services excel in the most complex and harsh conditions. Our employees develop customers for life through their daily commitment to expertise, productivity, and efficiency.

Learn more at www.irtools.com

