



Ingersoll Rand®

Precision Lifting with Advanced Control.

The **E-LIFT™ Series Electric Hoist** delivers smooth, precise lifting through advanced permanent magnet motor technology combined with VFD control. A unique pendant-mounted control knob enables infinitely variable low-speed adjustment within the dual-speed operation, giving operators unmatched accuracy for delicate positioning, along with the productivity of standard high-speed lifting.

Engineered for demanding environments, the Electric Hoist features a rugged cast aluminum housing with integrated cooling fins for superior heat dissipation. With IP55 protection for the hoist and IP65 protection for the pendant, it ensures reliable performance, durability, and reduced maintenance in tough industrial applications.

Designed to meet global safety and compliance requirements, the hoist is available with CE, UL, and CSA certifications, providing confidence for use across international markets and helping simplify specification, installation, and regulatory compliance.

E-LIFT™ Series Electric Hoist



Ingersoll Rand® E-LIFT™ Series Electric Hoist

Steel Hook
(Plain/Motorized/Trolley)

Motor & Housing

Chain Container

Electro-Galvanized Link Chain

Steel Hook
(Self-Locking Hook)

Two-Button Pendant
(Four-Button Pendant)

Variable Speed Knob



Model Number	Capacity (lbs)	Duty Rating (HMI/ISO)	Lifting Speed (ft/min)		Product Weight (lbs)	Rated Power (hp)	Headroom (in)
			Low (Variable)	High			
EVLK0501C10C06102L	1,102	H4/M5 (40% ED)	6.6 - 17	33	94	1.5	22.8
EVLK1001C10C06102L	2,205	H4/M5 (40% ED)	5.2 - 14	26	102	2	22.8
EVLK1002C10C06102L	4,409	H4/M5 (40% ED)	2.6 - 6.9	13	110	2	24.4
EVLK2001C10C06102L	4,409	H4/M5 (40% ED)	6.2 - 12	31	209	5	40.2
EVLK2501C10C06102L	5,512	H4/M5 (40% ED)	5.2 - 10	26	224	5	40.2
EVLK1502C10C06102L	6,614	H4/M5 (40% ED)	4.3 - 8.5	21	246	5	41.3
EVLK2502C10C06102L	11,023	H4/M5 (40% ED)	2.6 - 5.2	13	297	5	43.3
EVLK0501C10C06106L	1,102	H4/M5 (40% ED)	6.6 - 17	33	94	1.5	22.8
EVLK1001C10C06106L	2,205	H4/M5 (40% ED)	5.2 - 14	26	102	2	22.8
EVLK1002C10C06106L	4,409	H4/M5 (40% ED)	2.6 - 6.9	13	110	2	24.4
EVLK2001C10C06106L	4,409	H4/M5 (40% ED)	6.2 - 12	31	209	5	40.2
EVLK2501C10C06106L	5,512	H4/M5 (40% ED)	5.2 - 10	26	224	5	40.2
EVLK1502C10C06106L	6,614	H4/M5 (40% ED)	4.3 - 8.5	21	246	5	41.3
EVLK2502C10C06106L	11,023	H4/M5 (40% ED)	2.6 - 5.2	13	297	5	43.3

* first 7 models are 230V/3ph/60Hz, last 7 models are 460V/3ph/60Hz



Ingersoll Rand (NYSE:IR), driven by an entrepreneurial spirit and ownership mindset, is dedicated to helping make life better for our employees, customers, and communities. Customers lean on us for our technology-driven excellence in mission-critical flow creation and industrial solutions across 40+ respected brands where our products and services excel in the most complex and harsh conditions. Our employees develop customers for life through their daily commitment to expertise, productivity, and efficiency.

Learn more at
www.irttools.com

