

COMPRESSOR DATA SHEET

**Gardner
Denver**

In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors

Rotary Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR				
1	Manufacturer: Gardner Denver			
2	Model Number: L160RS-217.5hp-190psi		Date:	01/04/21
	☐ Air-cooled	☒ Water-cooled	Type:	Screw
			# of Stages:	1
3*	Full Load Operating Pressure ^b		190	psig ^b
4	Drive Motor Nominal Rating		218	hp
5	Drive Motor Nominal Efficiency		95.0	percent
6	Fan Motor Nominal Rating (if applicable)		0.34	hp
7	Fan Motor Nominal Efficiency		86.6	percent
8*	Input Power (kW)		Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d
	196.03		819.7	23.91
	180.58		749.7	24.09
	165.65		680.0	24.36
	151.09		610.6	24.74
	137.05		541.5	25.31
	123.24		472.7	26.07
9*	Total Package Input Power at Zero Flow ^{c, d}		25.0	kW
10	Isentropic Efficiency		73.04	%
11	Note: Graph is only a visual representation of the data in Section 8 Note: Y-Axis Scale, 10 to 35, + 5kW/100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity			

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator

Consult CAGI website for a list of participants in the third party verification program:

www.cagi.org

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:
- NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m^3 / min	ft^3 / min			
Below 0.5	Below 17.6	+/- 7	+/- 8	+/- 10%
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.1