



CompAir Genuine Service Kits

Valid from 02/2022

CompAir Genuine Service Kits are an **easy** and **cost-effective solution** for preventive maintenance or repairs on CompAir portable compressors. Each service kit is tailored to the needs of the product. It contains a set of original spare parts from CompAir, and in addition to maintenance intervals and downtime, also reduces the time spent on maintenance or repairs.

Your advantages:



All parts – **one package**



Longer lifetime



Practically straightforward,
just an order process



Compliance with
current standards



Reduce costs



Available through **CompAir's worldwide**
customer service network



Avoid downtime



Practical kits for easier main-
tenance and logistics planning

Model Serie Engine	Kit Part No	Service kit		Service plan		
		Description	Quantity per kit	Interval ¹⁾	Oil Motor ²⁾	Oil Airend ³⁾
 C10-12 – C14 DLT0101 Honda GX630	CC1186379	Portable Kit Motor C10-12 – C14				
		Engine air filter element	1 piece	Every 12 months or 300 hours	5W-30/10W-30 4 stroke – SJ or better C10-12 – C14 Synth below -15°	
		Engine oil filter	1 piece			
		Engine fuel filter	1 piece			
		Spark plug	2 pieces			
	CC1186378	Portable Kit Airend C10-12 – C14				
	Compressor air filter element	1 piece	Every 12 months or 600 hours		SCUO2000-20GT	
	Compressor oil filter	1 piece				
	Separator element	1 piece				
	O-Ring R 37	1 piece				
	O-Ring R 49	1 piece				
CC1186377	Portable Kit Airend C10-12 – C14			Heavy Duty		
	Compressor air filter element	1 piece	Every 3 months or 300 hours		SCUO2000-20GT	
	Compressor oil filter	1 piece				

¹⁾ Maintenance time intervals are based on operating hours or calendar date, whichever occurs first.

²⁾ SACO32-20 compressor oil is approved for use in every compressor model except for the DLT0207, and in ambient temperatures that do not consistently exceed 25°C

³⁾ SCUO2000-20GT compressor oil is approved for use in every compressor model (except for the DLT0207) used in ambient temperatures consistently above 25°C.



Model Serie Engine	Kit Part No	Service kit		Service plan		
		Description	Quantity per kit	Interval ¹⁾	Oil Motor ²⁾	Oil Airend ³⁾
 C20 – C30	PKM0206-1	Portable Kit Motor C20 – C30				
		Oil filter cartridge engine	1 piece	Every 6 months or 500 hours	ZS1216355-5L ZS1216356-20L ZS1216357-209L	
	Filter fuel line	1 piece				
	Fuelfilter element	1 piece				
DLT0206 Kubota D1105, V1505 from 05/2007	PKA0206-1	Portable Kit Airend C20 – C30				
		Exchange filter (oil filter)	1 piece	Every 12 months or 1,000 hours		SACO32-20 *SCUO2000-20GT
	Filter element air	1 piece				
	Fine separator	1 piece				
	Joint 110x140 x1,5 EL	2 pieces				
 C20 – C30	PKM0207-1	Portable Kit Motor C20 – C30				
		Spare cartr.Mot.Oil fil	1 piece	Every 3 months or 250 hours	ZS1216355-5L ZS1216356-20L ZS1216357-209L	
	Fuel filter	1 piece				
	Insert water separator	1 piece				
DLT0207 Yanmar 3TNV76U-DCP	PKA0207-1	Portable Kit Airend C20 – C30				
		Exchange filter (oil filter)	1 piece	Every 12 months or 1,000 hours		ZS1231213
	Filter element	1 piece				
	Fine separator	1 piece				
	Pipe seal R. 123.42x3.53	1 piece				
	FKM 70 Shore	2 pieces				
 C35 – C62	PKM0407-1	Portable Kit Motor C35 – C62				
		Spare cartr.Mot.Oil fil	1 piece	Every 6 months or 500 hours	ZS1216355-5L ZS1216356-20L ZS1216357-209L	
	Replacement cartridge/fuel filter	1 piece				
	Hose to fuel filter	1 piece				
DLT0407 Cummins A2300 from 08/2008 to 02/2011	PKA0407-1	Portable Kit Airend C35 – C42				
		Air filter insert	2 pieces	Every 12 months or 1,000 hours		SACO32-20 *SCUO2000-20GT
	Safety cartridge	2 pieces				
	Fine oil separator	1 piece				
	Seal 141x170 x1,5	2 pieces				
	Oil filter	1 piece				
	PKA0407-2	Portable Kit Airend C50				
	Air filter insert	2 pieces	Every 12 months or 1,000 hours		SACO32-20 *SCUO2000-20GT	
	Safety cartridge	2 pieces				
	Air-oil separ. element	1 piece				
	Seal	2 pieces				
	Oil filter	1 piece				
	PKA0407-3	Portable Kit Airend C62				
	Air filter insert	2 pieces	Every 12 months or 1,000 hours		SACO32-20 *SCUO2000-20GT	
	Safety cartridge	2 pieces				
	Air-oil separ. element	1 piece				
	Seal	2 pieces				
	Oil filter	1 piece				

¹⁾ Maintenance time intervals are based on operating hours or calendar date, whichever occurs first.

²⁾ SACO32-20 compressor oil is approved for use in every compressor model except for the DLT0207, and in ambient temperatures that do not consistently exceed 25°C

³⁾ SCUO2000-20GT compressor oil is approved for use in every compressor model (except for the DLT0207) used in ambient temperatures consistently above 25°C.



Model Serie Engine	Kit Part No	Service kit		Service plan		
		Description	Quantity per kit	Interval ¹⁾	Oil Motor ²⁾	Oil Airend ³⁾
 C35 – C50 DLT0408 Yanmar 4TNV88B- KCP from 02/2011	PKM0408-1	Portable Kit Motor C35 – C50				
		Spare cartr.Mot.Oil fil	1 piece	Every 6 months or 500 hours	ZS1216355-5L ZS1216356-20L ZS1216357-209L	
		Fuel filter DLT0408	1 piece			
		Insert water separator DLT0408	1 piece			
	PKA0408-1	Portable Kit Airend C35 – C42				
	Air filter insert	2 pieces	Every 12 months or 1,000 hours		SACO32-20 *SCUO2000-20GT	
	Safety cartridge	2 pieces				
	Fine oil separator	1 piece				
	Seal 141x170 x1,5	2 pieces				
	Oil filter	1 piece				
	Locking screw	1 piece				
PKA0408-2	Portable Kit Airend C50					
	Air filter insert	2 pieces	Every 12 months or 1,000 hours		SACO32-20 *SCUO2000-20GT	
	Safety cartridge	2 pieces				
	Air-oil separ. element	1 piece				
	Seal	2 pieces				
	Oil filter	1 piece				
	Locking screw	1 piece				
New Airend GD4 as from 03/2019	PKA0408-3	Portable Kit Airend C35–C42				
		Air filter insert	2 pieces	Every 12 months or 1,000 hours		SACO32-20 *SCUO2000-20GT
	Safety cartridge	2 pieces				
	Fine oil separator	1 piece				
	Seal 141x170 x1,5	2 pieces				
	Oil filter	1 piece				
	Locking screw	1 piece				
New Airend GD4 as from 03/2019	PKA0408-4	Portable Kit Airend C50				
		Air filter insert	2 pieces	Every 12 months or 1,000 hours		SACO32-20 *SCUO2000-20GT
	Safety cartridge	2 pieces				
	Air-oil separ. element	1 piece				
	Seal	2 pieces				
	Oil filter	1 piece				
	Locking screw	1 piece				

¹⁾ Maintenance time intervals are based on operating hours or calendar date, whichever occurs first.

²⁾ SACO32-20 compressor oil is approved for use in every compressor model except for the DLT0207, and in ambient temperatures that do not consistently exceed 25°C

³⁾ SCUO2000-20GT compressor oil is approved for use in every compressor model (except for the DLT0207) used in ambient temperatures consistently above 25°C.



Model Serie Engine	Kit Part No	Service kit		Service plan		
		Description	Quantity per kit	Interval ¹⁾	Oil Motor ²⁾	Oil Airend ³⁾
 C35 – C50 DLT0409 Yanmar 4TN- V98CT-NCP New airend GD4 on C50 as from 03/2019	PKM0409-1	Portable Kit Motor C35 – C50				
		Replacement cartridge/fuel filter	1 piece	Every 6 months or 500 hours	ZS1216355-5L ZS1216356-20L ZS1216357-209L	
		Filter cartridge (fuel preliminary filter)	1 piece			
		Sealing ring	1 piece			
		Spare cartr.Mot.Oil fil	1 piece			
	PKA0409-1	Portable Kit Airend C35–C42				
	Air filter insert	2 pieces	Every 12 months or 1,000 hours		SACO32-20 *SCUO2000-20GT	
	Safety cartridge	2 pieces				
	Fine oil separator	1 piece				
	Seal 141x170 x1,5	2 pieces				
	Oil filter	1 piece				
	Locking screw	1 piece				
PKA0409-2	Portable Kit Airend C50					
	Air filter insert	2 pieces	Every 12 months or 1,000 hours		SACO32-20 *SCUO2000-20GT	
	Safety cartridge	2 pieces				
	Air-oil separ. element	1 piece				
	Seal	2 pieces				
	Oil filter	1 pieces				
	Locking screw	1 piece				
 C55 – C76 DLT0704 Cummins B3 3TAA	PKM0704-1	Portable Kit Motor C55 – C76				
		Spare cartr.Mot.Oil fil	1 piece	Every 6 months or 500 hours	ZS1216355-5L ZS1216356-20L ZS1216357-209L	
		Replacement cartridge/fuel filter	1 piece			
		Hose to fuel filter	1 piece			
PKA0704-1	Portable Kit Airend C55 – C76					
	Filter element	2 pieces	Every 12 months or 1,000 hours		SACO32-20 *SCUO2000-20GT	
	Safety cartridge	2 pieces				
	Exchange filter	1 piece				
	Air-oil separ. element	1 piece				
	Seal	2 pieces				
 C55 – C76 DLT0704-R1 Cummins B3 3TAA	PKM0704-1	Portable Kit Motor C55 – C76				
		Spare cartr.Mot.Oil fil	1 piece	Every 6 months or 500 hours	ZS1216355-5L ZS1216356-20L ZS1216357-209L	
		Replacement cartridge/fuel filter	1 piece			
		Hose to fuel filter	1 piece			
	PKA0705-1	Portable Kit Airend C55 – C76				
		Filter element	2 pieces	Every 12 months or 1,000 hours		SACO32-20 *SCUO2000-20GT
	Safety cartridge	2 pieces				
	Exchange filter	1 piece				
	Air-oil separ. element	1 piece				
	Seal	2 pieces				

¹⁾ Maintenance time intervals are based on operating hours or calendar date, whichever occurs first.

²⁾ SACO32-20 compressor oil is approved for use in every compressor model except for the DLT0207, and in ambient temperatures that do not consistently exceed 25°C

³⁾ SCUO2000-20GT compressor oil is approved for use in every compressor model (except for the DLT0207) used in ambient temperatures consistently above 25°C.



Model Serie Engine	Kit Part No	Service kit		Service plan		
		Description	Quantity per kit	Interval ¹⁾	Oil Motor ²⁾	Oil Airend ³⁾
 <p>C55 – C76 DLT0705 Yanmar 4TN-V98CT-NCP from 12/2015 DLT0705-R1 Yanmar 4TNV98T-NCP from 02/2021</p>	PKM0705-1	Portable Kit Motor C55 – C76				
		Replacement cartridge/fuel filter	1 piece	Every 6 months or 500 hours	ZS1216355-5L ZS1216356-20L ZS1216357-209L	
		Filter cartridge (fuel preliminary filter)	1 piece			
		Sealing ring	1 piece			
	Spare cartr.Mot.Oil fil	1 piece				
	PKA0705-1	Portable Kit Airend C55 – C76				
		Filter element	2 pieces	Every 12 months or 1,000 hours		SACO32-20 *SCUO2000-20GT
		Safety cartridge	2 pieces			
		Air-oil separ. element	1 piece			
		Exchange filter oil	1 piece			
		Seal	2 pieces			
 <p>C85 – C140 DLT1303 Cummins QSB4.5 from 09/2007</p>	PKM1303-1	Portable Kit Motor C85 – C140				
		Fuel filter	1 piece	Every 6 months or 500 hours	ZS1216355-5L ZS1216356-20L ZS1216357-209L	
		Oil filter cartridge	1 piece			
		Filter cartridge (fuel preliminary filter)	1 piece			
	PKA1303-1	Portable Kit Airend C85 – C140				
		Air filter insert	2 pieces	Every 12 months or 1,000 hours		SACO32-20 *SCUO2000-20GT
		Safety cartridge	2 pieces			
		Oil filter cartridge	1 piece			
		Sealing ring	1 piece			
		Air-oil separ. element	1 piece			
		Pipe seal.R.	2 pieces			
from Q1/2019	PKA1303-2	Portable Kit Airend C85 – C140				
		Air filter insert	2 pieces	Every 12 months or 1,000 hours		SACO32-20 *SCUO2000-20GT
		Safety cartridge	2 pieces			
		Oil filter cartridge	1 piece			
		Sealing ring	1 piece			
		Air-oil separ. element	1 piece			
		Pipe seal.R.	2 pieces			
 <p>C85 – C140 DLT1304 Deutz TCD 4.1 L4 from 06/2017</p>	PKM1304-1	Portable Kit Motor C85 – C140				
		Rep. Cartridge/fuel filter	1 piece	Every 6 months or 500 hours	ZS1216355-5L ZS1216356-20L ZS1216357-209L	
		Rep. Cartridge/oil filter	1 piece			
		Filter element/fuel prefilter	1 piece			
	PKA1304-1	Portable Kit Airend C105 – C140				
		Air filter element	2 pieces	Every 12 months or 1,000 hours		SACO32-20 *SCUO2000-20GT
		Oil filter element	1 piece			
		Rep. Cartridge/adblue filter	1 piece			
		Safety cartridge	2 pieces			
		Fine separator	1 piece			
		Pipe seal.R.	2 pieces			
	PKA1304-2	Portable Kit Airend C85 – C110				
		Air filter element	2 pieces	Every 12 months or 1,000 hours		SACO32-20 *SCUO2000-20GT
		Oil filter element	1 piece			
		Rep. Cartridge/adblue filter	1 piece			
		Safety cartridge	2 pieces			
		Fine separator	1 piece			
		Pipe seal.R.	2 pieces			
GD5						

¹⁾ Maintenance time intervals are based on operating hours or calendar date, whichever occurs first.

²⁾ SACO32-20 compressor oil is approved for use in every compressor model except for the DLT0207, and in ambient temperatures that do not consistently exceed 25°C

³⁾ SCUO2000-20GT compressor oil is approved for use in every compressor model (except for the DLT0207) used in ambient temperatures consistently above 25°C.



Model Serie Engine	Kit Part No	Service kit		Service plan				
		Description	Quantity per kit	Interval ¹⁾	Oil Motor ²⁾	Oil Airend ³⁾		
 C200 – C270 DLT2701/2701-R1/2702/2703 Cummins QSB6.7 from 01/2008 GD-M1/GD-M2	PKM270X-1	Portable Kit Motor C200 – C270						
		Sp.Cartr.Fuel filter	1 piece	Every 3 months or 250 hours	ZS1216355-5L ZS1216356-20L ZS1216357-209L			
	Filter element	1 piece						
	Oil filter cartridge	1 piece						
 C200TS-24 C210TS-21 C230TS-17 Cummins QSB6.7 from 09/2014 GD-M1/GD-M2	PKA270X-1	Portable Kit Airend C200 – C270						
		Oil filter cartridge	1 piece	Every 12 months or 1,000 hours		SACO32-20 *SCUO2000-20GT		
	Air filter insert	2 pieces						
	Safety cartridge	2 pieces						
	Air-oil separ. element	1 piece						
	Seal	2 pieces						
 C200TS-24 C210TS-21 C230TS-17 Cummins QSB6.7 from 09/2014 GD-M1/GD-M2	PKA270XHP-1	Portable Kit Airend C200 – C230 HP						
		Oil filter cartridge	2 pieces	Every 6 months or 500 hours		SACO32-20 *SCUO2000-20GT		
DLT2701HP/2702HP Cummins QSB6.7 from 09/2014 GD-M1/GD-M2	PKA270XHP-2	Portable Kit Airend C200 – C230 HP						
		Air filter insert	2 pieces				Every 12 months or 1,000 hours	
		Safety cartridge	2 pieces					
		Oil filter cartridge	2 pieces					
	Air-oil separ. element	1 piece						
	Seal	2 pieces						
 C200 – C270 DLT2701-R1 Cummins QSB6.7 GD-M1	PKM270X-1	Portable Kit Motor C200 – C270						
		Sp.Cartr.Fuel filter	1 piece	Every 3 months or 250 hours	ZS1216355-5L ZS1216356-20L ZS1216357-209L			
	Filter element	1 piece						
	Oil filter cartridge	1 piece						
 C200TS-24 C210TS-21 C230TS-17 DLT2701/2701 HP-R1 Cummins QSB6.7 GD-M1	PKA270X-1	Portable Kit Airend C200 – C270						
		Oil filter cartridge	1 piece	Every 12 months or 1,000 hours		SACO32-20 *SCUO2000-20GT		
	Air filter insert	2 pieces						
	Safety cartridge	2 pieces						
	Air-oil separ. element	1 piece						
	Seal	2 pieces						
 C200TS-24 C210TS-21 C230TS-17 DLT2701/2701 HP-R1 Cummins QSB6.7 GD-M1	PKA270XHP-1	Portable Kit Airend C200 – C230 HP						
		Oil filter cartridge	2 pieces	Every 6 months or 500 hours		SACO32-20 *SCUO2000-20GT		
DLT2701/2701 HP-R1 Cummins QSB6.7 GD-M1	PKA270XHP-2	Portable Kit Airend C200 – C230 HP						
		Air filter insert	2 pieces				Every 12 months or 1,000 hours	
		Safety cartridge	2 pieces					
		Oil filter cartridge	2 pieces					
	Air-oil separ. element	1 piece						
	Seal	2 pieces						

¹⁾ Maintenance time intervals are based on operating hours or calendar date, whichever occurs first.

²⁾ SACO32-20 compressor oil is approved for use in every compressor model except for the DLT0207, and in ambient temperatures that do not consistently exceed 25°C

³⁾ SCUO2000-20GT compressor oil is approved for use in every compressor model (except for the DLT0207) used in ambient temperatures consistently above 25°C.