





OMI Ecoplus Oil Water Separators Overview

The OMI Ecoplus Oil Water Separators combine cutting-edge multi-stage filtration with a planet-friendly design, all under one comprehensive product range. Covering flow capacities from 2 m³/min up to 60 m³/min, these separators help you meet strict disposal regulations while maximizing operational efficiency.


OMI Ecoplus separators use advanced oil-adsorption technology and carefully selected activated carbon to bring residual oil content down to below 5 ppm. Each model is designed with both performance and the environment in mind. Housings are manufactured from high-grade recycled materials, aligning with modern sustainability goals. Add in simplified maintenance steps—such as quick-test valves, overflow indicators, and optional monitoring sensors—and you'll find OMI Ecoplus is a reliable, eco-forward choice for any compressed air setup.



Easy maintenance



User-friendly



Environmentally friendly





OMI Ecoplus Oil Water Separators Specifications

Element life indicator, offering you a visual indication of the element life status

Model	Max. Compressor Capacity	Max. Oil Absorption Volume	Filter Elements	Activated Carbon Elements	Inlet Connection	Outlet Connection	Residual Oil Content	DIBt Certification	Housing Material	Housing Color	Lid Color
Ecoplus 20	2 m ³ /min (70 CFM)	2 liters	1	1	1/2" (10 mm)	1/2" (14 mm)	<5 ppm	Yes	PPC	Black	Blue
Ecoplus 45	4.5 m ³ /min (160 CFM)	3.5 liters	1	1	1/2" (10 mm)	1/2" (14 mm)	<5 ppm	Yes	PPC	Black	Blue
Ecoplus 100	10 m ³ /min (350 CFM)	10 liters	1	1	1/2" (10 mm)	1" (26 mm)	<5 ppm	Yes	PE	Black	Blue
Ecoplus 200	20 m ³ /min (750 CFM)	15 liters	1	1	1/2" (10 mm)	1" (26 mm)	<5 ppm	Yes	PE	Black	Blue
Ecoplus 300	30 m ³ /min (1250 CFM)	25 liters	2	2	1/2" (10 mm)	1" (26 mm)	<5 ppm	Yes	PE	Black	Blue
Ecoplus 600	60 m ³ /min (2500 CFM)	50 liters	2	2	1/2" (10 mm)	1" (26 mm)	<5ppm	Yes	PE	Black	Blue

