

REFRIGERATED COMPRESSED AIR DRYER

MODEL:

ESD2250W 400/3/50

Rated capacity*

Flow rate	m ³ /h	2250	
	l/min	37500	
	cfm	1324,3	
Inlet air temperature	°C / °F	35 / 95	(Min 5 / 41 ÷ Max 60 / 140)
Outlet air temperature	°C / °F	27 / 81	(Max 40 / 104)
Water temperature	°C / °F	29,4 / 84	(Min 15 / 59 ÷ Max 40 / 104)
Water consumption	m ³ /h	3,1	(Max 11,69)
Working pressure	bar / psi	7,0 / 102	(Min 3 / 44 ÷ Max 14 / 203)
Pressure drop	bar / psi	0,25 / 3,63	(Max 0,36 / 5,22)
Pressure dew point	°C / °F	3 / 37	
Power consumption	kW	3,5	(Max 7,25)
Power supply	V/Ph/Hz	400/3/50	(±10% / -- / ±1)
Rated adsorption	A	7,18	(Max 12,29)
Lock Rotor Ampere	A	50	
Weight	kg / Lbs	428 / 944	
Air connections	IN/OUT	3" BSP	
Water connections	IN/OUT	1"1/2 BSP	
Water pressure	bar / psi	Min. 2 / 29 - Max. 10 / 145	
Ambient temperature	°C / °F	25 / 77	(Min 2 / 36 ÷ Max 46 / 115)
Sound pressure level	DB(A)	< 70	
Coolant type	Type / kg / t CO ₂	R513A / 5,5 Kg / 3,473	

Standard features

Control panel:	<i>Electronic system type</i>	Separator type:	<i>Demister type</i>
Condenser:	<i>Water cooled, shell and tube</i>	Compressor type:	<i>Hermetic type</i>
Water flow regulator:	<i>Pressostatic valve</i>	Glycol circulator:	<i>Centrifugal</i>
Heat exchanger:	<i>Aluminium brazed plate</i>	Installation location:	<i>Indoor</i>
Expansion method:	<i>Capillary tube</i>	Drain discharge:	<i>No loss (Smart drain)</i>

* Performances refer to air suction of FAD 20°C (68°F), 1 bar (14.5 psig), and the following operating conditions: 7 bar (100 psig) working pressure, 3°C (37°F) pressure dewpoint, 29.4°C (84.9°F) water temperature, 35°C (95°F) compressed air inlet temperature.

Performances & specifications: +/- 5%