

REFRIGERATED COMPRESSED AIR DRYER

MODEL:

ED 600 230/1/50

Rated capacity*

Flow rate	m ³ /h	600	
	l/min	10000	
	cfm	353,1	
Inlet air temperature	°C / °F	35 / 95	(Min 5 / 41 ÷ Max 60 / 140)
Outlet air temperature	°C / °F	27 / 81	(Max 47 / 117)
Ambient temperature	°C / °F	25 / 77	(Min 2 / 36 ÷ Max 50 / 122)
Working pressure	bar / psi	7,0 / 101,5	(Min 3 / 44 ÷ Max 16 / 232)
Pressure drop	bar / psi	0,21 / 3,05	(Max 0,34 / 4,93)
Pressure dew point	°C / °F	3 / 37	
Power supply	V/Ph/Hz	230/1/50	(±10% / -- / ±1)
Rated power consumption	kW	1,01	(Max 1,26)
Rated adsorption	A	5,25	(Max 5,68)
Lock Rotor Ampere	A	31	
Condenser cooling air flow rate	m ³ /h	2800	
Condenser max heat rejection	kW	6	
Weight	kg / Lbs	134 / 295	
Air connections	IN/OUT	2" BSP	
Coolant type	Freon / kg / t CO ₂	R513A / 1,40 / 0,884	

Standard features

Control panel:	Electronic system type	Separator type:	Demister type
Condenser cooling:	Air cooled	Compressor type:	Hermetic type
Ventilator motor:	Suction fan	Installation location:	Indoor
Heat exchanger:	Aluminium brazed plate	Drain discharge:	No loss drain
Expansion method:	Capillary tube + by-pass	Electric protection:	IP 42

* Performances refer to air suction of FAD 20°C (68°F), 1 bar (14.5 psig), and the following operating conditions: 7 bar (100 psig) working pressure, 3°C (37°F) pressure dewpoint, 25°C (77°F) ambient temperature, 35°C (95°F) compressed air inlet temperature.

Performances & specifications: +/- 5%

