

REFRIGERATED COMPRESSED AIR DRYER

MODEL:

ED 4800 400/3/50

Rated capacity*

Flow rate	m ³ /h	4800	
	l/min	80000	
	cfm	2826,9	
Inlet air temperature	°C / °F	35 / 95	(Min 5 / 41 ÷ Max 60 / 140)
Outlet air temperature	°C / °F	27 / 81	(Max 40 / 104)
Ambient temperature	°C / °F	25 / 77	(Min 2 / 36 ÷ Max 46 / 115)
Working pressure	bar / psi	7,0 / 101,5	(Min 3 / 44 ÷ Max 14 / 203)
Pressure drop	bar / psi	0,3 / 4,35	(Max 0,36 / 5,22)
Pressure dew point	°C / °F	3 / 37	
Power supply	V/Ph/Hz	400/3/50	(±10% / -- / ±1)
Rated power consumption	kW	6,81	(Max 11,29)
Rated adsorption	A	14,81	(Max 20,29)
Lock Rotor Ampere	A	145	
Condenser cooling air flow rate	m ³ /h	12000	
Condenser max heat rejection	kW	38	
Weight	kg / Lbs	465 / 1.025	
Air connections	IN/OUT	DN 150 PN16	
Coolant type	Freon / kg / t CO ₂	R513A / 6,3 / 3,98	

Standard features

Control panel:	Electronic system type	Separator type:	Demister type
Condenser cooling:	Air cooled	Compressor type:	Hermetic type
Ventilator motor:	Suction fan	Installation location:	Indoor
Heat exchanger:	Aluminium brazed plate	Drain discharge:	No loss (Smart drain)
Expansion method:	Capillary tube + by-pass	Electric protection:	IP 42

* Performances refer to air suction of FAD 20°C (68°F), 1 bar (14.5 psig), and the following operating conditions: 7 bar (100 psig) working pressure, 3°C (37°F) pressure dewpoint, 25°C (77°F) ambient temperature, 35°C (95°F) compressed air inlet temperature.

Performances & specifications: +/- 5%

	Air in		Power supply		Air flow
	Air out		Condensate outlet		

