

REFRIGERATED COMPRESSED AIR DRYER

MODEL:

ESD 54 230/1/50

Rated capacity*

Flow rate	m ³ /h	54
	l/min	900
	cfm	31,8

Inlet air temperature	°C / °F	35 / 95	(Max 60 / 140)
Outlet air temperature	°C / °F	27 / 81	(Max 47 / 117)
Ambient temperature	°C / °F	25 / 77	(Max 50 / 122)
Working pressure	bar / psi	7,0 / 102	(Max 16 / 232)
Pressure drop	bar / psi	0,09 / 1,3	(Max 0,34 / 4,9)
Pressure dew point	°C / °F	3 / 37	
Power consumption	kW	0,24	(Max 0,31)
Power supply	V/Ph/Hz	230/1/50	(±10% / -- / ±1)
Rated adsorption	A	1,49	(Max 1,81)
Lock Rotor Ampere	A	11,6	
Weight	kg / Lbs	37 / 82	
Air connections	IN/OUT	1/2"	
Coolant type	Freon / kg / t CO ₂	R513A / 0,16 / 0,101	

Standard features

Control panel:	Electronic system type	Separator type:	Demister type
Condenser cooling:	Air cooled	Compressor type:	Hermetic type
Ventilator motor:	Pusher fan	Installation location:	Indoor
Heat exchanger:	Aluminium plate - 3 Layers	Drain discharge:	No loss (Smart drain)
Glycol circulator:	Centrifugal	Electric protection:	IP 42
Expansion method:	Capillary tube		

* Performances refer to air suction of FAD 20°C (68°F), 1 bar (14.5 psig), and the following operating conditions: 7 bar (100 psig) working pressure, 3°C (37°F) pressure dewpoint, 25°C (77°F) ambient temperature, 35°C (95°F) compressed air inlet temperature.

Performances & specifications: +/- 5%

