

HeatSink

TRUE-CYCLING REFRIGERATED
COMPRESSED AIR DRYERS

HeatSink dryers are designed to take advantage of normal fluctuations in compressed air demand and ambient conditions. Thermal Mass technology stores cooling energy and allows the refrigeration system to automatically cycle off during periods of low demand, while the dryer continues to remove moisture and contaminants from the compressed air stream.

Integrated Filtration – Complete Air Treatment Solution

ZEKS brings yet another patented innovation to compressed air dryers with our unique, integrated prefilter and afterfilter design. Users can easily access the dryer's filter elements from the side of the unit without removing panels or disturbing pipework. And since the filters are integral to the dryer, installation costs are reduced.

Independently Verified Performance

Through participation in the Compressed Air and Gas Institute (CAGI) Performance Verification Program, actual performance and energy consumption of 50-1000 scfm ZEKS HeatSink dryers have been independently validated against CAGI Data Sheets.



- ✓ R513A for smaller frames and R454B for larger frames deliver a 50% reduction in global warming potential (GWP) compared to legacy models.
- ✓ Minimum refrigeration charge enhances sustainability
- ✓ Electronically Commutated (EC) Fan motors modulate fan speed to achieve optimal efficiency

Uses

**R-513A
& R-454B**

Refrigerant

www.zeks.com



HeatSink

TRUE-CYCLING REFRIGERATED COMPRESSED AIR DRYERS

Standard Features

Integrated Filtration

- Complete air treatment solution

Multi-Layer Heat Exchanger

- Integrated precool / reheater reduces energy consumption
- Low pressure drop

Timed Solenoid Condensate Drain

- Efficient condensate removal

Galvanized Internal Structure

- Corrosion-resistant

Tested to the Latest Standards

- Listed to UL 60335-1 & 60335 2-40



Advanced Digital Controller

- Refrigerant pressure display
- Filter element replacement notification
- Maintenance reminders
- Ethernet connectivity

Microchannel Condenser

- Minimizes refrigerant charge
- Increased efficiency

Powder Coated Enclosure

- Industrial grade protection

ISO 8573-1 Class 4 PDP

- Designed & tested at 38°F

Optional Features

- NEMA 4 – Liquid tight construction for falling and hose-directed water
- DPC Plus – Enhanced controller provides inlet / outlet temperature and pressure readings
- No-Air Loss Drain - Conserves compressed air energy – factory installed, internally mounted

ZEKS Models	Capacity SCFM*	Overall Dimensions				Ship Weight		In/Out Air Connect Size	Drain Connect	Operating kW**		Refrige. Type	Max Working Pressures	Voltages
		W IN.	D IN.	H (AC) IN.	H (WC) IN.	AC LBS.	WC LBS.			AC	WC			
300HSH	300	34.0	49.2	55.6	48.1	875	815	2" MNPT	1/4" FNPT	2.40	1.50	R-513A	200 PSIG	460/3/60
400HSH	400	34.0	49.2	55.6	48.1	895	840	2" MNPT	1/4" FNPT	3.00	1.90	R-513A	200 PSIG	460/3/60
500HSG	500	41.4	57.5	59.8	53.4	1341	1299	3" MNPT	1/4" FNPT	2.70	2.20	R-513A	200 PSIG	460/3/60
600HSG	600	41.4	57.5	59.8	53.4	1366	1325	3" MNPT	1/4" FNPT	2.90	2.60	R-513A	200 PSIG	460/3/60
700HSG	700	41.4	57.5	59.8	53.4	1391	1349	3" MNPT	1/4" FNPT	4.40	3.60	R-513A	200 PSIG	460/3/60
800HSG	800	41.4	57.5	59.8	53.4	1416	1376	3" MNPT	1/4" FNPT	4.80	4.00	R-513A	200 PSIG	460/3/60

ZEKS Models	Capacity SCFM*	Overall Dimensions			Ship Weight LBS.	In/Out Air Connect Size IN.	Operating kW**	Refrigerant Type	Max Working Pressures	Voltages
		W IN.	D IN.	H IN.						
1000HSGA	1000	40.7	78.9	82.5	1928	4	8.8	R-454B	200 PSIG	460/3/60
1200HSGA	1200	40.7	78.9	82.5	1928	4	9.8	R-454B	200 PSIG	460/3/60
1600HSGA	1600	40.7	78.9	82.5	1928	4	12.5	R-454B	200 PSIG	460/3/60
1000HSGW	1000	40.7	78.9	72.2	1964	4	7.8	R-454B	200 PSIG	460/3/60
1200HSGW	1200	40.7	78.9	72.2	1964	4	8.6	R-454B	200 PSIG	460/3/60
1600HSGW	1600	40.7	78.9	72.2	1964	4	10.2	R-454B	200 PSIG	460/3/60

* Performance based on ISO 7183, table 2, option A2. (100 psig inlet air pressure; 100°F inlet air temperature; 100°F ambient air temperature)

** Average kilowatts per hour of dryer operation at full rated capacity. NEMA 1 electrical, standard



ZEKS HeatSink™ compressed air dryers are not designed, intended or approved for breathing air applications.

Specifications, illustrative materials and descriptions contained herein were as accurate as known at the time this publication was approved for printing. The company reserves the right to change specifications, discontinue models, equipment or design without notice and without incurring obligation. The information set out in this brochure is for preliminary information only and is not intended to constitute any representation or warranty by ZEKS to potential customers or to form the basis of a contract with any customer.