



# 1" D-HANDLE IMPACT WRENCH

2850MAX & 2850MAX-6

## **POWERED UP, NOT WEIGHED DOWN**

### Ingersoll Rand® 2850MAX 1" D-handle Impact Wrench

With 2,100 ft lbs of torque, the new Ingersoll Rand® 2850MAX 1" D-handle Impact Wrench is our fiercest 1" wrench yet, loaded with extreme power that lasts as long as you need and continuously delivers over time. This sturdy yet lightweight impact wrench powers through bolts other tools can't. With a steel core, precision machined impact mechanism and powerful motor, the 2850MAX is solid enough to handle REAL WORK day in and day out without sacrificing power over time. But even with all that high-performance steel, the 2850MAX is still 25% lighter than the industry's leading 1" wrench, so it's easy to maneuver and causes less fatigue. No matter how tough the job, you can power through with the 2850MAX.



**Heavy Truck & Tire Changing** 



**Industrial Maintenance** 



**Heavy Equipment** 



**Ergonomics** 

At 21.58 lbs, 25% lighter than the industry's leading 1" wrench

Vehicle Repair

Highly engineered design delivers the

power you need over the life of the tool

#### **TOOL FEATURES**

#### **DURABILITY -**

Chemical resistant housing & steel core design stand up to drops and harsh work environments

#### POWER -

Solid steel impact mechanism delivers 2,100 ft lbs of torque



#### REACH

6" extended anvil increases accessibility in hard to reach places (2850MAX-6) Standard anvil option available, (2850MAX)



#### CONTROL -

360° adjustable side handle rotates fully around the tool as the job demands



**RELIABILITY** 

#### 3

#### **ACCESSIBILITY**

Swivel hose connection keeps cords from getting tangled so you can move freely around the work

#### **SPECS**

2850MAX & 2850MAX-6 1" IMPACTOOL™								
Model	Drive Size, Type	Max Forward Torque ftlb. (Nm)	Max Reverse Torque ftlb. (Nm)	ВРМ	Free Speed (rpm)	Weight Ib (kg)	Length in. (mm)	Sound Level dB(A)
2850MAX	1"	2000 (2715)	2100 (2850)	770	5500	19.41 (8.8)	13.1 (334)	96.7
2850MAX-6	1" - 6 inch	2000 (2715)	2100 (2850)	770	5500	21.58 (9.8)	19.1 (486)	96.7



