

REFRIGERATED COMPRESSED AIR DRYER

MODEL:

TUNDRA 1530 400/3/50

Rated capacity*

Flow rate	m ³ /h	2600	
	l/min	43333	
	cfm	1530,3	
Inlet air temperature	°C / °F	35 / 95	(Max 60 / 140)
Outlet air temperature	°C / °F	27 / 81	(Max 47 / 117)
Ambient temperature	°C / °F	25 / 77	(Max 46 / 115)
Working pressure	bar / psi	7,0 / 101,5	(Max 14 / 203)
Pressure drop	bar / psi	0,3 / 4,35	(Max 0,36 / 5,22)

Power supply	V/Ph/Hz	400/3/50	(±10% / -- / ±1)
Rated power consumption	kW	4,55	(Max 6,31)
Rated adsorption	A	7,68	(Max 11,69)
Lock Rotor Ampere	A	87	
Weight	Kg / Lbs	260 / 573	
Air connections	IN/OUT	3" BSP	
Coolant type	Freon	R407C	

Standard features

Control panel:	Electronic system type	Separator type:	Demister type
Condenser cooling:	Air cooled	Compressor type:	Hermetic type
Ventilator motor:	Suction fan	Installation location:	Indoor
Heat exchanger:	Aluminium brazed plate	Drain discharge:	No loss (Smart drain)
Expansion method:	Capillary tube + by-pass	Electric protection:	IP 42

* Performances refer to air suction of FAD 20°C (68°F), 1 bar (14.5 psig), and the following operating conditions: 7 bar (100 psig) working pressure, 3°C (37°F) pressure dewpoint, 25°C (77°F) ambient temperature, 35°C (95°F) compressed air inlet temperature.

Performances & specifications: +/- 5%

 Air in	 Power supply	 Air flow
 Air out	 Condensate outlet	

