





**OBERDORFER®**

An Ingersoll Rand Business

## N3000E Series Bronze Pedestal Rotary Gear Pumps

Model OBN3000E



Model OBN3000RE

### Features

- 3/8" BSPT Ports
- Temp. Range: -40 - 204°C
- Bronze Corrosion Resistant Castings
- Special Cast Bronze Gears
- Stainless Steel Shafts & Fasteners
- Formed Ring Seal Packing, Lipseal & Mechanical Seal Options
- Heavy Duty Carbon Bearings (Self Lubricating)
- Positive Displacement Flow


### Liquids and Temperature

Service life will be increased substantially if the liquid pumped is clean and has some degree of lubricity. These positive displacement pumps have tight tolerances. Fine abrasives like sand, silt, or powders in suspension will accelerate pump wear and reduce throughput.

Liquids compatible with bronze and stainless steel can be pumped providing proper seal has been specified (see chemical compatibility or check factory). When possible, flush the pump after each usage.

Temperature extremes are detrimental to service life and should be avoided. Basic metals of construction allow a temperature range of -40 to 204°C. Some lip and mechanical seal elastomers have a limit of 100°C. (see engineering data or check factory). Allowing a liquid to freeze in the pump can cause damage.

### Performance




### By-Pass and Rotation

The pump by-pass is not intended to be a metering or flow control device. Its main purpose is to function as a pressure relief when the desired set point is exceeded, overheating can occur within 5 -10 minutes if the discharge line is completely shut off for extended periods.

Reversing rotation reverses the "IN" and "OUT" ports and the location of the by-pass ports have to be reversed.

The by-pass valve is factory set at 3.5 bar. To increase the setpoint, turn the by-pass valve adjusting screw in a clockwise direction.





**OBERDORFER®**

An Ingersoll Rand Business




## Suction Lift

Close tolerances and the positive pumping action make the rotary gear pump capable of lifting water on the suction side as high as 6 meters. Though gear pumps are self priming, a foot valve is recommended. If possible, wet the gears with liquid to be pumped for the first dry start. Liquid retained in the system and gear chambers serves to "wet" the pump on subsequent starts.

## Drive

Either direct drive with flexible coupling or pulley drive can be used. Make sure both flexible coupling halves are properly aligned. When using a pulley, do not overtighten the belt. Also, to absorb belt side thrust at higher pressures and larger size pumps, an external ball bearing support is recommended - consult factory.

## Dimensions



**Ingersoll Rand**

12500 South Pulaski Road  
Alsip, IL 60803, USA  
Phone (800) 448.1668




## Parts List

Seal Arrangement	1	2	3	4	5*	6	7	8	9	10	11	12	13	14	15
Model	Seal Arrangement	Qty. 1	Qty. 2	Qty. 1	Qty. 4	Qty. 1	Qty. 1	Qty. 1	Qty. 8	Qty. 1	Qty. 1	Qty. 1	Qty. 1	Qty. 1	Qty. 1
OBN3000E	Packing	OB1762	OB5479	NA	OB9318NC1N	OB5091	OB33001	OB33002	OB9797-041	OB9322NN5N	OB5385	NA	NA	NA	NA
OBN3000ES3	Buna Lip	NA	NA	OB5463	OB9318NC2N	OB5091	OB33001	OB33002	OB9797-041	OB9322NN5N	OB5385	NA	NA	NA	NA
OBN3000ES15	Viton Lip	NA	NA	OB9997	OB9318NC2N	OB5091	OB33001	OB33002	OB9797-041	OB9322NN5N	OB5385	NA	NA	NA	NA
OBN3000ES16	Buna Bellows Mech.	OB5374	NA	OB32202	OB9372NC9N	OB5091	OB33045	OB33002	OB9797-041	OB9322NN5N	OB5385	NA	NA	NA	NA
OBN3000ES17	Viton Bellows Mech.	OB5374	NA	OB32235	OB9372NC9N	OB5091	OB33045	OB33002	OB9797-041	OB9322NN5N	OB5385	NA	NA	NA	NA
OBN3000ES18	Teflon Wedge Mech.	OB5374	NA	OB32923	OB9372NC6N	OB5091	OB33045	OB33002	OB9355-041	OB9322NN5N	OB5385	NA	NA	NA	NA
Relief Valve Versions: OBN3000RE, OBN3000RES3, OBN3000RES15, OBN3000RES16, OBN3000RES17, OBN3000RES18								OB9323NN5B		OB5206	OB5205	OB5207	OB5200	OB5209D	OB5204

Items 8 and 10-17 for the R versions only.

Item 23 is only used on OBN3000ES15 pumps.

Item 20 is only used on OBN3000ES18 pumps.



	16	17	18	19	20	21	22	23	Repair Kit*
Model	Qty. 2	Qty. 1	Qty. 2	Qty. 1	Qty. 1	Qty. 1	Qty. 2	Qty. 1	
OBN3000E	NA	NA	OB8885	NA	NA	OB9344	OB9345	NA	OB10636
OBN3000ES3	NA	NA	OB8885	NA	NA	OB9344	OB9345	NA	OB11350
OBN3000ES15	NA	NA	OB8885	NA	NA	OB9344	OB9345	OB3033	OB12105
OBN3000ES16	NA	NA	OB8885	OB5382	NA	OB9344	OB9345	NA	OB12134
OBN3000ES17	NA	NA	OB8885	OB5382	NA	OB9344	OB9345	NA	OB12135
OBN3000ES18	NA	NA	OB8885	OB5382	OB6052	OB9344	OB9345	NA	OB12136
Relief Valve Versions	OB9797-021	OB9797-018							

\* Repair kit contains 2, 4, 5, 6 and 7