

FIXTURE POLE WITH 3"x5"
REINFORCED HAND HOLE
& COVER, ROTATED 90°
FROM LUMINAIRE, 12"
ABOVE BASE COVER

2 POLE BUSSMAN #HEX
FUSE HOLDER OR EQUAL
WITH 5A FUSES OR SIZED
PER MANUFACTURES
SPECIFICATIONS FOR
LUMINAIRE INLINE FUSING

GROUND LUG
BEHIND HAND
HOLE

BASE COVER

CHAMFER EDGE 3/4"

FOUR ANCHOR BOLTS
FURNISHED WITH POLE

CLAMP CONNECTION
(TYPICAL)

#5 RE-BAR

#2 TIES AT 12" OC

1" PVC CONDUIT
24" DEEP MINIMUM

REFER TO FIXTURE
SCHEDULE FOR HEIGHT

3'-0"

FINISHED GRADE

AS REQUIRED

20'-0" OF #8 BARE CU
WIRE COILED

24" ϕ

NOTE: THIS DETAIL IS SHOWN FOR
ELECTRICAL INFORMATION ONLY. THE
POLE/FIXTURE MANUFACTURER SHALL
PROVIDE STRUCTURAL CALCULATIONS.



LIGHT POLE

REV. NO. 002

REV. DATE : 04-15-21

DRAWN BY : R Montoya

DWG. NO.

ELD-004

SCALE : NTS